

Date: 28 November 2013

Information Sheet No.: TDS00650

BOSTIK IDENDEN T301 SELF-ADHESIVE REINFORCED FOIL TAPE

Bostik Idenden T301 Self-Adhesive Reinforced Foil Tape is part of the market leading range of products for the heating, ventilation and air conditioning sectors. Bostik Idenden T301 is a bright aluminium foil tape reinforced with 5 mm² glass scrim. The tape is coated with a high tack rubber/resin adhesive system and protected by a removable release paper. The reinforced foil improves mechanical damage resistance and is ideal for matching the foil finish on insulation. It is easy to apply, exhibiting instant adhesion and can be moulded to any profile. The final bond has high shear strength and the foil promotes the optimum balance of surface conformity and tensile strength. This makes it ideal for lap sealing foil faced insulation materials, metal and duct sealing and other general purpose applications. Before using this product refer to the relevant Health & Safety Sheet.

Features

- High standards of reliability, strength and durability
- High tack adhesive
- Consistent performance over a wide temperature range

Product Characteristics

Finish Bright aluminium foil tape reinforced with 5mm² glass scrim

Adhesive Rubber/resin

Release paper High quality siliconised paper

Product Code **662094** 45m x 50mm x 24
662124 45m x 75mm x 16

Shelf life/storage 12 months from date of manufacture when stored unopened in a cool, dry place within the temperature range +10°C to +30°C

Typical Performance Data (approx.)

Service temperature -10°C to +90°C

Application temperature -5°C (minimum)

Ultimate tensile strength approximately 90 N/25mm² (aluminium only)

Elongation Minimum 7% (aluminium only) (approx.)

Peel adhesion to steel Initial: 20-25 N/25mm
24 hours: 25-30 N/25mm (approx.)

Directions for use

IMPORTANT

Before using Bostik Idenden T301 Self-Adhesive Reinforced Foil Tape refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

Preparation

1. Surfaces to be bonded must be clean, dry and free from dust, grease and loose materials. If necessary, wipe surfaces sparingly with a cloth dampened with a ketone-free cleaner such as Evo-Stik Cleaner 4 and allow to dry for at least an hour before tape application.
2. The butt joints of insulation sections should be positioned together without gaps to ensure an adequate bond.
3. Select a tape width suitable for the application. A width of 50 mm is suitable for closely positioned, flat sections. Otherwise, select a tape the thickness of the insulation plus 50 mm to allow for the exposed cut edge.
4. Remove the release paper from a section of the tape, taking care not to touch the adhesive surface.

Align the tape centrally over the joint. Pull the tape taut and then press down well over the entire joint area. Rub the tape to remove any wrinkles or folds.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Idenden T301 Self-Adhesive Reinforced Foil Tape.

Precautions in Use

Bostik Idenden T301 Self-Adhesive Reinforced Foil Tape is intended for joint sealing applications only, and is therefore not suitable for use where the joint is subject to mechanical stress. In this instance, insulation should be fixed using a suitable adhesive or hanger system.

Sales & Technical contacts at Bostik	Telephone	Facsimile	Email addresses
Sales	0844 371 1192	01785 241818	customer.service@bostik.com
Technical advice	0844 371 1197	01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) sheets	01785 272625	01785 212962	stafford.gatehouse@bostik.com

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.