



PRODUKTEGENSKAPER

- Isolert
- Tåler temperaturer fra -45 °C til +105 °C
- Med klick-lås for enkel montering

NRF	Dimensjon	Varetekst
3485257	11,5X15MM	Isoklammer
3485259	11,5X18MM	Isoklammer
3485261	12X22MM	Isoklammer
3485262	12,5X28MM	Isoklammer
3485264	13X35MM	Isoklammer
3485266	13,5X42MM	Isoklammer
3485275	13,5X48MM	Isoklammer
3485277	13,5X54MM	Isoklammer
3485282	14X64MM	Isoklammer
3485284	14X76MM	Isoklammer
3485299	14,5X89MM	Isoklammer
3485302	15X114MM	Isoklammer
3485303	17X15MM	Isoklammer
3485304	17,5X18MM	Isoklammer
3485305	18X22MM	Isoklammer
3485307	19X28MM	Isoklammer
3485308	19,5X35MM	Isoklammer
3485311	20,5X42MM	Isoklammer
3485312	21X54MM	Isoklammer
3485314	22X76MM	Isoklammer
3485315	22,5X89MM	Isoklammer

Installasjon

1. Plasser den isolerende kragen rundt røret.
2. Lim kragen sammen rundt skjøten
3. Forsegl med den klebende tapen
4. Skru fast klammeret rundt den isolerende kragen
5. Lim klammeret fast i isolasjonen

